

# 14-(G)CCR SERIES CARBON BRIQUETTE 'CYST REMOVAL' FILTER CARTRIDGE

## APPLICATION:

- Reduces chlorine taste and odour
- Suitable for reduction of cysts
- Excellent polishing filter
- Ideal for potable water in residential, industrial, commercial and food service applications

## SPECIFICATION:

- Temperature Range: 40°F to 180°F (4.4°C to 82.2°C)
- Filter media: Powder Activated Carbon Impregnated Cellulose
- Filter core: Polypropylene
- End Caps: Vinyl Plastisol
- Netting: Polypropylene



DIMENSIONS					
Part No.	Pentek Model No.	Micron	Flow Rate	Chlorine	Weight
		Rating	PSI Drop @ GPM	Capacity	grams
<b>STANDARD</b>					
14-CCR1-0.5	CBC-10	0.5	1.3 PSI @ 1 GPM	20,000 Gal. @ 1 GPM*	529
14-CCR2-0.5	CBC-20	0.5	3 PSI @ 2 GPM	45,000 Gal. @ 2.3 GPM*	567
14-GCCR1-0.5	CBC-BB	0.5	7 PSI @ 4 GPM	50,000 Gal. @ 2 GPM*	1418
14-GCCR2-0.5	CBC20-BB	0.5	8.5 PSI @ 4 GPM	150,000 Gal. @ 7 GPM*	3175

\* Estimated capacity using 2ppm FAC (Free Available Chlorine) at continuous flow with greater than 90% reduction.

DIMENSIONS							
Part No.	Pentek Model No.	Inner Diameter		Outer Diameter		Length	
		inches	mm	inches	mm	inches	mm
<b>STANDARD</b>							
14-CCR1-0.5	CBC-10	1.00	25.40	2.75	69.85	9.88	250.83
14-CCR2-0.5	CBC-20	1.00	25.40	2.75	69.85	20.00	508.00
14-GCCR1-0.5	CBC-BB	1.00	25.40	4.50	114.30	10.00	254.00
14-GCCR2-0.5	CBC20-BB	1.00	25.40	4.50	114.30	20.00	508.00

**Always Test Water** - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

**Change Out** - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

**BOSHART**  
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0  
Tel: 800-561-3164

[boshart.com](http://boshart.com) ♦ [blog.boshart.com](http://blog.boshart.com)