

# 14-IM SERIES ICEMAKER / IN-LINE TASTE AND ODOUR FILTER

## APPLICATION:

- Designed to remove unpleasant tastes and odours as well as sediment
- Low pressure drop and steady flow rates
- Easy in-line installation and suitable for automatic icemaker, reverse osmosis, coffee maker, water dispensers
- Integral post filter to remove small carbon fines and other sediment

## SPECIFICATION:

- Max Temperature Rating: 110°F (43°C)
- Max Pressure Rating: 125 PSI
- Filter media: Coconut Shell Activated Carbon
- Filter media: Polypropylene post filter
- Filter body: Polypropylene



DIMENSIONS										
Part No.	Connection	Outer Diameter		Length		Flow Rate	Service Life (approx)			Weight
		inches	mm	inches	mm	GPM	Months	Gallons	Litres	grams
14-IM2.5X12-02	1/4" FPT	2.50	63.50	12.00	304.80	0.8	10	3500	13249	400
14-IM2X10-02QC	1/4" o.d. Quick Connect	2.00	50.80	10.00	254.00	0.4	6	2000	7570	300
14-IM2X6-02QC	1/4" o.d. Quick Connect	2.00	50.80	6.00	152.40	0.4	5	1000	3785	280

**Always Test Water** - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

**Change Out** - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

**BOSHART**  
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0  
Tel: 800-561-3164

[boshart.com](http://boshart.com) ♦ [blog.boshart.com](http://blog.boshart.com)