

14-SWNC SERIES STRING WOUND NATURAL COTTON FILTER CARTRIDGE

APPLICATION:

- Suitable for filtration of liquids with temperatures up to 300°F (149°C) including potable water when used in conjunction with stainless steel filter housings
- For removing very fine sediment through to very coarse sediment in a wide range of filtering applications

SPECIFICATION:

- Manufactured from natural cotton fibres wound onto a tin core
- Diagonally wound pattern provides maximum surface area for efficient particle filtration
- Max Temperature Rating: 300°F (149°C)
- Filter media: Natural cotton
- Filter core: Tin



DIMENSIONS									
Part No.	Inner Diameter		Outer Diameter		Length		Micron	Flow Rate	Weight
	inches	mm	inches	mm	inches	mm	Rating	PSI Drop @ GPM	grams
STANDARD									
14-SWNC1-05	1.00	25.40	2.50	63.50	9.88	250.83	5	1 PSI @ 5 GPM	210
14-SWNC1-10	1.00	25.40	2.50	63.50	9.88	250.83	10	1 PSI @ 10 GPM	210
14-SWNC1-20	1.00	25.40	2.50	63.50	9.88	250.83	20	1 PSI @ 20 GPM	210
14-SWNC1-25	1.00	25.40	2.50	63.50	9.88	250.83	25	1 PSI @ 25 GPM	210
14-SWNC1-50	1.00	25.40	2.50	63.50	9.88	250.83	50	1 PSI @ 50 GPM	212
14-SWNC2-05	1.00	25.40	2.50	63.50	20.00	508.00	5	1 PSI @ 10 GPM	420
14-SWNC2-10	1.00	25.40	2.50	63.50	20.00	508.00	10	1 PSI @ 20 GPM	420
14-SWNC2-20	1.00	25.40	2.50	63.50	20.00	508.00	20	1 PSI @ 40 GPM	420

Always Test Water - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

Change Out - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

BOSHART
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 800-561-3164

boshart.com ♦ blog.boshart.com