

WHAT'S NEW?

HEAD CASTING ELONGATED

Custom machining allows stand pipe to be screwed on further, covering the threading entirely and eliminating rusting and corrosion issues.

COLOUR & MARKINGS

New Gold reflects Boshart's updated branding and allows for easy identification of the new design.

EXTENDED HEX

Hex extended below the locking pad allows for easier grip of head casting when servicing.

NEW VALVE BODY

Dual flow passages allow for more flow capacity and precision machining engages full thread length into valve body.

7/8" PLUNGER


Smaller plunger allows for increased clearance during maintenance.

3/4" FPT INLET CONNECTION

High capacity valves bodies (3/4" and 1") have been discontinued.

OTHER CHANGES

- Updated Hex Coupling and Connecting Rod
- 1/8" Street Elbow Included



WHAT'S STAYING?

DESIGNED, ENGINEERED & ASSEMBLED AT BOSHART

Producing premium yard hydrants since 2003, our assembly equipment ensures proper torque and with precise alignment of the drain port on every yard hydrant.

BUILT TO LAST

Heavy duty casting has a large flow channel and lengthened handle with ample room for comfortable operating.

HIGHEST FLOW RATES

A full flow through inlet with a sweeping bend flow passage in the head casting minimizes friction loss.

DUAL HANDLE LOCKING

Includes two locking features as standard. The handle can be locked with a padlock.

ALL STAINLESS-STEEL HARDWARE

The handle bolt and nut, set screw, operating rod and flow rate locking thumb bolt are all stainless steel, ensuring longer life.

MORE FEATURES

Easy to Adjust
Smooth Operation
Low Maintenance & Easy Repair
Quality Standpipe

EMBRACE THE NEW HUE! FROST-FREE YARD HYDRANTS



BOSHART
INDUSTRIES

YHBR SERIES

- Galvanized Stand Pipe
- No-Lead Bronze Valve Body
- 3/4" FPT Inlet



YHSS SERIES

- 304 Stainless Steel Stand Pipe
- 304 Stainless Steel Valve Body
- 3/4" FPT Inlet



HYDRANT DIMENSIONAL SPECIFICATIONS

| YHBR Series | YHSS Series | Bury Depth (ft) | Stand Pipe Length (in) | Overall Hydrant Length (in) |
|-------------|-------------|-----------------|------------------------|-----------------------------|
| YHBR-01 | YHSS-01 | 1 | 36 | 45 |
| YHBR-015 | YHSS-015 | 1.5 | 42 | 51 |
| YHBR-02 | YHSS-02 | 2 | 48 | 57 |
| YHBR-03 | YHSS-03 | 3 | 60 | 69 |
| YHBR-04 | YHSS-04 | 4 | 72 | 81 |
| YHBR-05 | YHSS-05 | 5 | 84 | 93 |
| YHBR-06 | YHSS-06 | 6 | 96 | 105 |
| YHBR-07 | YHSS-07 | 7 | 108 | 117 |
| YHBR-08 | YHSS-08 | 8 | 120 | 129 |
| YHBR-10 | YHSS-10 | 10 | 144 | 153 |
| YHBR-13 | | 13 | 180 | 189 |

Determining Length Required: The water source and hydrant base must be below the frost line. This depth is known as the "bury". (Frost line will vary by location.)

i.e. Our 4' bury hydrants have a 6' stand pipe which is buried 4' underground with approximately 22" clearance between ground level and the spout.

FITTINGS AND INSTALLATION ACCESSORIES



Hydrant Elbows & Tees

- Available in No-Lead Bronze & 304 Stainless
- Extra long and reducing options



Ball Valves

- Available in No-Lead Bronze & 304 Stainless



Gear Clamps

- Marine Grade - All 300 Series Stainless Steel



Thread Sealants

- P.T.F.E Tapes
- Gray Magic Thread Seal Compound

BOSHART
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 519-595-4444 Fax: 519-595-4380 Toll Free: 800-561-3164
© Copyright 2023 Boshart Industries Inc. All Rights Reserved. Printed in Canada 2023



For more information on installation, adjustment, repair & operation, visit Boshart Knowledge Base at

[SUPPORT.BOSHART.COM](https://support.boshart.com)

