

# 14-(G)CW SERIES CARBON WRAP TASTE AND ODOUR CARTRIDGE

## APPLICATION:

- Dual-purpose cartridge to reduce bad taste & odour, chlorine taste & odour, and fine particles or sediment
- Effective chlorine reduction and good dirt holding capacity
- Suitable for residential chlorinated water supplies
- High flow rates make this an economical cartridge for a wide range of applications

## SPECIFICATION:

- Temperature Rating: 40-125°F (4.4-51.7°C)
- Filter media: Powder Activated Carbon Impregnated Cellulose
- Filter core: Polypropylene
- End Caps: Vinyl Plastisol
- Netting: Polypropylene



DIMENSIONS					
Part No.	Pentek Model No.	Micron	Flow Rate	Chlorine	Weight
		Rating	PSI Drop @ GPM	Capacity	grams
<b>STANDARD</b>					
14-CW478-05	C2	5	2 PSI @ 2 GPM	>2,500 @ 0.5 GPM	123
14-CW1-05	C1	5	4 PSI @ 5 GPM	>5,000 @ 1 GPM	215
14-CW2-05	C1-20	5	1 PSI @ 5 GPM	>10,000 @ 2 GPM	390
<b>GIANT</b>					
14-GCW1-05	NCP-BB	10	2 PSI @ 8 GPM	500 @ 2 GPM	738
14-GCW2-05	C1-20BB	5	2 PSI @ 4 GPM	>40,000 @ 4 GPM	1633

DIMENSIONS							
Part No.	Pentek Model No.	Inner Diameter		Outer Diameter		Length	
		inches	mm	inches	mm	inches	mm
<b>STANDARD</b>							
14-CW478-05	C2	1.00	25.40	2.50	63.50	4.87	123.82
14-CW1-05	C1	1.00	25.40	2.87	73.02	9.75	247.65
14-CW2-05	C1-20	1.00	25.40	2.50	63.50	20.00	508.00
<b>GIANT</b>							
14-GCW1-05	NCP-BB	1.00	25.40	4.50	114.30	9.75	247.65
14-GCW2-05	C1-20BB	1.00	25.40	4.50	114.30	20.00	508.00

Always Test Water - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.  
Change Out - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

**BOSHART**  
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0  
Tel: 800-561-3164

[boshart.com](http://boshart.com) ♦ [blog.boshart.com](http://blog.boshart.com)