

14-(G)SWBC SERIES STRING WOUND BLEACHED COTTON FILTER CARTRIDGE

APPLICATION:

- Suitable for filtration of liquids with temperatures up to 300°F (149°C)
- For removing very fine sediment through to very coarse sediment in a wide range of filtering applications including potable water

SPECIFICATION:

- Manufactured from bleached cotton fibres wound on to a 304 stainless steel core
- Diagonally wound pattern provides maximum surface area for efficient particle filtration
- Max Temperature Rating: 300°F (149°C)
- Filter media: Bleached cotton
- Filter core: Stainless Steel



DIMENSIONS									
Part No.	Inner Diameter		Outer Diameter		Length		Micron	Flow Rate	Weight
	inches	mm	inches	mm	inches	mm	Rating	PSI Drop @ GPM	grams
STANDARD									
14-SWBC1-05	1.00	25.40	2.50	63.50	9.88	250.83	5	1 PSI @ 5 GPM	212
14-SWBC1-10	1.00	25.40	2.50	63.50	9.88	250.83	10	1 PSI @ 10 GPM	212
14-SWBC1-50	1.00	25.40	2.50	63.50	9.88	250.83	50	1 PSI @ 50 GPM	197
14-SWBC2-05	1.00	25.40	2.50	63.50	20.00	508.00	5	1 PSI @ 10 GPM	423
14-SWBC2-10	1.00	25.40	2.50	63.50	20.00	508.00	10	1 PSI @ 20 GPM	423
GIANT									
14-GSWBC1-05	1.00	25.40	4.50	114.30	10.00	254.00	5	1 PSI @ 12 GPM	850
14-GSWBC1-10	1.00	25.40	4.50	114.30	10.00	254.00	10	1 PSI @ 13 GPM	850
14-GSWBC2-05	1.00	25.40	4.50	114.30	20.00	508.00	5	1 PSI @ 22 GPM	1665
14-GSWBC2-10	1.00	25.40	4.50	114.30	20.00	508.00	10	1 PSI @ 24 GPM	1700

Always Test Water - Do not use this product with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the filtration system.

Change Out - Replacement filter cartridges have a limited service life. Changes in taste, colour and flow of the water (other liquid) being filtered are signals that replacement of the cartridge may be necessary.

BOSHART
INDUSTRIES

25 Whaley Avenue, PO Box 310, Milverton, ON CANADA N0K 1M0
Tel: 800-561-3164

boshart.com ♦ blog.boshart.com

© 2020 Boshart Industries Inc. All Rights Reserved.

BII-14-(G)SWBC-0620(2624)