SPDK(U) SERIES - UNIVERSAL SUMP PUMP DISCHARGE KIT

APPLICATION:

 Temporary or permanent sump pump water discharge

FEATURES:

- Cutting pads in 6' intervals
- Tubing has annular interior & exterior corrugations

SPECIFICATIONS:

- Conforms to ASTM D3350 Polyethylene Plastics Pipe & Fittings
- Conforms to ASTM F667 Corrugated Polyethylene Pipe & Fittings
- 24 feet of 1-1/4" polyethylene corrugated hose
- Kit includes two MPT x Barb adapters to connect sump pumps with 1-1/4" FPT or 1-1/2" FPT discharge connections
- Includes one clamp, 301 S.S. band and housing, 5/16" wide, 1/4" hex head carbon steel screw.

MATERIAL LIST				
Part Name	Material			
Tubing	High Density Polyethylene (HDPE)			
Adapters	Polypropylene			
Clamp	301 Stainless Steel band & housing, carbon steel screw			



DIMENSIONS							
Part No.	Tubing		Male Adapters	Weight			
	ID	Length	Size (Boshart Part No.)	lbs / foot	grams / foot		
SPDKU125-24	1-1/4"	24'	(1) 1-1/4" x 1-1/2" (34-SPHA-1512) and (1) 1-1/4" (34-SPHA-12)	0.800	36.29		



25 Whaley Avenue, PO Box 310, Milverton, ON CANADA NOK 1M0 Tel: 800-561-3164

VISIT US ONLINE AT BOSHART.COM



© 2025 Boshart Industries Inc. All Rights Reserved.