PA-NL SERIES NO LEAD BRONZE **PITLESS ADAPTER**

APPLICATIONS:

■ Designed to make raising a submersible pump for service or replacement easier

FEATURES:

- Heavy duty castings
- Large gaskets ensure positive seal to well casing
- Chamfered slide for easy installation
- Double drop pipe model available


SPECIFICATION:

- Threads conform to ANSI/ASME B1.20.1
- Fits 4-1/2" to 12" I.D. casing sizes

CERTIFICATION:

- NSF/ANSI Standard 61 Certified (Drinking Water System Components - Health Effects)
- NSF/ANSI Standard 372 Certified (Drinking Water System Components - Lead Content)
- Water Systems Council listed PAS-97 (2017)*
















DIMENSIONS													
Part No.	Drop Pipe Size	Casing Size I.D.	Hole Saw Size	Replac	Working Load	н		L		w		Weight	
	Inches	Inches	Inches	Standard	Part No.	lbs	in	mm	in	mm	in	mm	grams
Single Drop Pipe													
PA-800NL	1	5 - 12	1-3/4	AS568-324	09-PA-100-OR-324	900	2.84	72.14	4.35	110.49	2.72	69.09	1334
PA-100NL *						2000	2.77	70.36	4.47	113.54	2.66	67.56	1432
PA-125NL *	1-1/4	5 - 12	2-1/8	AS568-326	09-PA-125-OR-326	2000	3.15	80.01	5.16	131.06	3.15	80.01	2389
PA-200NL *	2	5-5/8 - 12	3-1/8	AS568-332	09-PA-200-OR-332	5000	4.75	120.65	6.76	171.70	4.55	115.57	6380
Double Drop Pipe - allows for two pipes to go down the well, generally used in jet pump applicaitons													
PA-2XNL *	1 & 1-1/4	4-1/2 - 12	1-3/4 & 2-1/8	AS568-325	09-PA-2X-ORK	2000	6.40	162.56	5.06	128.52	3.73	94.74	3670

^{*} These parts certified under Water Systems Council listed PAS-97 (2017)



25 Whaley Avenue, PO Box 310, Milverton ON CANADA NOK 1M0 Tel: 800-561-3164

VISIT US ONLINE AT BOSHART.COM

